2000 Slide Switches - up to 5 position 10A 250Vac

- Slide switches
- Ratings up to 16A, 250V ac
- PCB and solder terminals
- 2, 3, 4 and 5 position
- Choice of circuits
- Choice of actuators

10A 250Vac T85
6(3)A 250Vac T85

UL CSA 16A 250Vac Non Inductive
UL CSA 4A 300Vac
UL 65°C, file no. E45221, CSA file no. LR10990

RoHS compliant

μ contact gap

Please specify: Standard action (SP116) or Light action (SP118).
2000 series lubrication is inorganic and does not degrade plastics.

Technical data on pages 4 & 5.

T 2 2 20 5 C ---

TERMINAL SERIES POSITIONS CIRCUIT SLIDER BODY PRINT, COLOUR, ETC

TERMINAL

K


2.8 x 0.8

R


2.8 x 0.8

T


Solder

X


PCB 0.8 Sq.

Y


PCB 0.8 Sq.
For mounting stability switches have extra "support" terminals

* Nominal - Dimension varies with body type. For exact figure call sales

SERIES

2

POS'N

2 Switching positions

3 Switching positions

4 Switching positions

5 Switching positions

CIRCUIT

Viewed from back

2 positions	3 positions	4 positions	5 positions
10	10	10	10
20	20	20	20
30	30	30	30
40	40	40	40

SLIDER

0


6


D


L Limited travel on 2 pos


1 Not 2 position


7


E Limited travel on 2 pos


N


2


9


G Not 2 position


P Limited travel on 2 pos


3


A


H


R


4


B Not 2 position


J Not 2 position


S Limited travel on 2 pos


5 Also with legend


C


K Limited travel on 2 pos


T


X22205C ---

T2220EC ---



T23206A ---

T24306A ---

T25302A ---

T25100A ---

BODY

C 2 positions



H 2 positions



A 3 positions



H 3 positions



A 4 positions



H 4 positions



A 5 positions



OPTIONS

Colour
For custom slider colours call sales. A full range is available for large orders

DIMENSIONS (mm)

2 Position C body



2 Position H body



Cut-out/PCB Matrix



for PCB

3 Position A body



3 Position H body





for PCB

4 Position A body



4 Position H body





for PCB

5 Position A body





for PCB